# valspar if it matters, we're on it.®

# SAFETY DATA SHEET

Revision date 22-Feb-2016

Version 7

Supersedes Date: 27-Jan-2016

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier	
Product Code	U32
Product Name	LIME GREEN

Other means of identification No information available

Recommended use of the chemical and restrictions on use Tint, colorant

Details of the supplier of the safety data sheet See section 16 for more information

The Valspar Corporation PO Box 1461 Minneapolis, MN 55440

E-mail address

msds@valspar.com

Emergency telephone number United States of America 1-888-345-5732 American Samoa, Guam, Northern Mariana Islands, Puerto Rico, U.S. Virgin Islands 1-800-255-3924

# Section 2: HAZARDS IDENTIFICATION

# **Classification**

Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

Product Code U32 Page 1/10 AGHS - USA OSHA SDS



#### Signal word

DANGER

### HAZARD STATEMENTS

Flammable liquid and vapor May cause an allergic skin reaction Suspected of causing cancer May be fatal if swallowed and enters airways May cause drowsiness or dizziness

#### PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### RESPONSE

IF exposed or concerned: Get medical advice/attention.

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### Skin

If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

#### STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

#### DISPOSAL

Dispose of contents/containers in accordance with local regulations.

#### HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Not applicable.

#### **OTHER HAZARDS**

Causes mild skin irritation. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

# Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Titanium dioxide	13463-67-7	10 - 25
n-Butyl acetate	123-86-4	5 - 10
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	5 - 10
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - 3
Naphthalene	91-20-3	0.3 - 1

Product Code U32 Page 2/10 AGHS - USA OSHA SDS

Proprietary Additive	UNKNOWN	0.3 - 1
2-Hydroxyethyl methacrylate	868-77-9	0.1 - 0.3
Dipentene	138-86-3	0.1 - 0.3
Ethylbenzene	100-41-4	0.1 - 0.3

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

# Section 4: FIRST AID MEASURES

#### First Aid Measures

#### **General advice**

IF exposed or concerned: Get medical advice/attention.

#### Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### Skin Contact

If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

#### Most important symptoms and effects, both acute and delayed

Symptoms No information available.

#### Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

# Section 5: FIRE FIGHTING MEASURES

#### Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

#### Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

#### Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

# Section 6: ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

#### **Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

#### For emergency responders

Use personal protection recommended in Section 8.

#### Environmental precautions

Product Code U32 Page 3/10 AGHS - USA OSHA SDS Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

#### Methods and material for containment and cleaning up

#### Methods for containment

Prevent further leakage or spillage if safe to do so.

#### Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

# Section 7: HANDLING AND STORAGE

#### Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

#### **General Hygiene Considerations**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

#### Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

#### Incompatible materials

Strong oxidizing agents.

# Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> STEL: 15 ppm STEL: 75 mg/m <sup>3</sup>

Product Code U32 Page 4/10 AGHS - USA OSHA SDS

_				
Γ	Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
	100-41-4		TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm
				TWA: 435 mg/m <sup>3</sup>
				STEL: 125 ppm
				STEL 545 mg/m <sup>3</sup>

#### Appropriate engineering controls

#### **Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Tight sealing safety goggles.

#### Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

#### **Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### **Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

# **Thermal Protection**

No information available

# Section 9: PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Appearance Odor Color Odor Threshold pH value Melting point/freezing point Boiling point / boiling range flash point evaporation rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit: Lower flammability limit:	liquid No information available Solvent green No information available No information available No information available No information available No information available No information available No information available
Vapor Pressure	No information available
vapor density	No information available
Density (lbs per US gallon)	9.49
specific gravity	1.14
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

Product Code U32 Page 5/10 AGHS - USA OSHA SDS

#### **Other information**

# Section 10: STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous polymerization	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Hydrogen chloride.

# Section 11: TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Eye contact Not applicable Skin Contact May cause an allergic skin reaction Ingestion May be fatal if swallowed and enters airways Inhalation May cause drowsiness or dizziness

#### Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
n-Butyl acetate 123-86-4	= 14.13 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat)4 h
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m³ (Rat)4 h
Solvent naphtha, petroleum, light aromatic 64742-95-6	-	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat)4 h
Naphthalene 91-20-3	= 1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 340 mg/m³(Rat)1 h
Proprietary Additive UNKNOWN	-	-	-
2-Hydroxyethyl methacrylate 868-77-9	= 5050 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	-
Dipentene 138-86-3	-	-	-
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat)4 h

#### Numerical measures of toxicity - Product Information

UNKNOWN ACUTE TOXICITY 0%

0% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

# **Carcinogenicity**

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		х
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	х
Ethylbenzene 100-41-4	A3	Group 2B		Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen.

IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans.

NTP (National Toxicology Program) Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen. OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation	Not applicable
Serious eye damage/eye irritation	Not applicable
Skin sensitization	May cause an allergic skin reaction
Respiratory sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	Suspected of causing cancer
Reproductive Toxicity	Not applicable
Specific target organ toxicity (single exposure)	e May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure)	Not applicable
Aspiration hazard	Not applicable

# Section 12: ECOLOGICAL INFORMATION

#### Ecotoxicity

Harmful to aquatic life with long lasting effects.

Environmental precautions	Prevent product from entering drains.
Persistence and degradability No information available	2
Bioaccumulation No information available	
<u>Mobility</u> No information available	
Other adverse effects	No information available
	Section 13: DISPOSAL CONSIDERATIONS
Waste treatment methods	
Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.
	Section 14: TRANSPORT INFORMATION

DOT

IMDG

ΙΑΤΑ

Product Code U32 Page 7/10 AGHS - USA OSHA SDS

14.1 UN/ID no 14.2 Proper shipping name	UN1263 Paint related material	UN1263 Paint related material	UN1263 Paint related material
14.3 Hazard Class 14.4 Packing Group 14.5 Environmental hazard Not	3 III applicable	3 	3 
14.6 Special Provisions	B1, B52, IB3, T2, TP1, TP29 Emergency Response Guide Number 128	163, 223, 955 <b>EmS-No</b> F-E, S-E	A3, A72

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

# Section 15: REGULATORY INFORMATION

#### International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

All components are listed or exempt from listing. All components are listed or exempt from listing

# US Federal Regulations

Chemical Name	SARA 313 - Threshold Values %	Hazardous air pollutants (HAPs) content
Naphthalene	0.1	Present
91-20-3		
0.3 - 1		
Ethylbenzene	0.1	Present
100-41-4		
0.1 - 0.3		

SARA 311/312	Hazard	Categories
--------------	--------	------------

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate 123-86-4	5000 lb			Х
Naphthalene 91-20-3	100 lb	Х	Х	Х
Ethylbenzene 100-41-4	1000 lb	Х	Х	Х

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
n-Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Naphthalene 91-20-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

#### US State Regulations

#### Rule 66 status of product

Photochemically reactive.

#### **California Proposition 65**

WARNING! This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

#### U.S. EPA Label information EPA Pesticide registration number Not applicable

# U.S. State Right-to-Know Regulations

Chemical Name	
Proprietary Non-Hazardous Ingredient - Pr	roprietary CAS
Proprietary Non-Hazardous Ingredient - Pr	roprietary CAS
Titanium dioxide 13463-67-7	
n-Butyl acetate 123-86-4	
Solvent naphtha, petroleum, heavy a 64742-94-5	aromatic
Proprietary Non-Hazardous Ingredient - Proprietary Non-Hazardous Ingredient - Province Proprietary Proprietary Non-Hazardous Ingredient - Proprietary Non-Hazardous Ingredient	roprietary CAS
Proprietary Non-Hazardous Ingredient - Pr	roprietary CAS
C.I. Pigment Green 7 1328-53-6	
Solvent naphtha, petroleum, light a 64742-95-6	romatic
Naphthalene 91-20-3	
Ethylbenzene 100-41-4	

#### Section 16: OTHER INFORMATION

HMIS Health hazards * = Chronic Health Hazard Flammability Physical hazards Personal Protection	3* 3 0 X
Supplier Address Valspar Coatings 701 Shiloh Rd. Garland, TX 75042 972-276-5181	
Duran and J Dur	Draduat Sta

**Prepared By** 

Product Stewardship

**Revision date Revision Note** Disclaimer

22-Feb-2016 No information available

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

> Product Code U32 Page 9/10 AGHS - USA OSHA SDS

End of Safety Data Sheet

Product Code U32 Page 10 / 10 AGHS - USA OSHA SDS